

Index

Note: Page numbers followed by “*f*” and “*t*” refer to figures and tables, respectively.

A

- Acrylonitrile butadiene styrene, 5
- Additive manufacturing (AM)
 - biopolymers, 74–75
 - advanced biopolymer-based composite, 91–109
 - cellulose nanocrystals, 79–80
 - hydroxyapatite, 81–82
 - mechanical performance of, 83–90
 - morphed graphene, 80–81
 - nanodiamond, 78–79
 - physical performance of, 83
 - natural *vs* synthetic polymers, 76–77
- Advanced composite materials
 - challenges, 205–206
 - damage, 185–188
 - detection methods, 188–191
 - radiographic testing, 189
 - thermography, 189–191
 - ultrasonic testing, 189
 - visual inspection, 188–189
 - injection repair resin, 191–194
 - bismaleimides, 193
 - cyanate esters, 193
 - cianoacrylates, 193
 - epoxy resin, 192–193
 - polyester resin, 194
 - polyimides, 193
 - vinyl ester resin, 194
 - injection repair state-of-the-art showcases, 199–205
 - injection repair for artificial delamination, 203–205
 - pressure and vacuum-assisted injection repair, 199–200
 - vacuum-assisted resin injection device, 201–203, 203*f*
 - resin injection procedure
 - injection, 194–195
 - injection process, 196–198
 - postinjection process, 199
 - preinjection preparation, 195–196
 - vent holes, 194–195
- Aerospace industry, 276
- Agglomeration, 109
- AHP method, 131
- Alginate acid, 248
- American Society of Testing and Materials (ASTM), 57–58
- Amylopectin, 44*t*
- Amylose, 44*t*
- Aramid fiber, 6
- Artocarpus heterophyllus*, 148
- Automotive industries
 - applications, 20
 - automobile
 - chassis, 11–12
 - exteriors, 11–12
 - lightweight design, 12
 - mechanical properties, 12–20, 15*f*
 - composites manufacturing methods
 - blow molding, 10–11
 - extrusion, 10
 - foam molding technique, 11
 - injection molding, 10
 - thermoforming, 11
 - high-performance plastics in, 3
 - polymeric materials
 - acrylonitrile butadiene styrene, 5
 - chloride of polyvinyl, 5
 - general classification, 4
 - PMMA, 6
 - polyamide, 5
 - polybutylene terephthalate, 6
 - polycarbonate, 6
 - polyethylene, 5

Automotive industries (*Continued*)

- polyethylene terephthalate, 6
- polyoxymethylene, 6
- polypropylene, 4
- polystyrene, 5
- polyurethane, 5
- reinforcement, 6–7
 - aramid fiber, 6
 - basalt fiber, 7
 - carbon fiber, 7
 - glass fiber, 7
 - modification, 8–10

Automotive industry, 276

BBarely visible impact damage (BVID),
183–184

- Boeing classifies, 185
- delaminations subsequent of, 186–187

Basalt fiber, 7

 β -chitin, 80Biobased thermoplastic elastomer (BTPE),
91f

Biocompatibility, 219–220

Biocomposites

- in biomedical sectors, 145–148
- fracture modeling, 229–237
- mechanical properties of, 138–145
- sustainable biopolymer composites,
214–229
 - biocompatibility, 219–220
 - biodegradability, 216–219
 - recyclability, 220–225
 - self-healing, 226–229

Biodegradability, 216–219

Biofilms, 223–225

Biomaterials, 73–74, 132–134

- for plastic films, 246–247
- poly(3-hydroxybutyrate-co-3-hydroxyvalerate), 134
- polyhydroxybutyrate, 134
- polylactic acid, 133
- poly-L-lactide, 133–134
- thermoplastic starch, 132

Biopolymer-based soil treatment (BPST),
124

Biopolymers, 74–75

- advanced biopolymer-based composite,
91–109

application of, 44–47

- cellulose acetate, 116
- cellulose nanocrystals, 79–80
- characterization, 44–47
- classification of, 27, 28f, 29t
- for constructions and structural
applications, 123–126
- fabrication, 28–33
- failure, 33–34
- fiber reinforcement, 119
- green composites, 39–40
 - basic failure mechanisms in, 61
 - characterization of selected, 58–60
 - compression molding technique, 57–58
 - fiber length, 62–63
 - fiber properties, 61–62
 - hand lay-up technique, 55–56
 - impact damage, 63–64, 64f
 - reaction injection molding, 56–57, 57f
 - resin transfer molding technique, 56,
56f

hydroxyapatite, 81–82

matrix failure mechanisms, 64–65

mechanical performance of, 83–90

morphed graphene, 80–81

nanodiamond, 78–79

natural fibers, 117

- characterization of, 50–53
 - pseudo-stem banana fibers, 47–48
 - sisal fibers, 48
 - surface treatment of, 48–50

and origin, 114

particulate reinforcement, 120

physical performance of, 83

poly(3-hydroxybutyrate), 114–115

poly(3-hydroxybutyrate-co-3-hydroxyvalerate), 115

poly(L-lactic) acid, 115–116

polylactic acid, 115

preparation, 28–33

processing of, 40–43

repairing, 34–35

synthetic, 27–28

techniques

- compression molding, 121
- extrusion, 120–121
- filament winding, 122
- foam molding, 123
- injection molding, 121

- pultrusion, 121
- resin transfer molding, 122
- in situ polymerization, 120
- spray-up, 123
- thermoforming, 121
- thermoplastic starch, 116
- Bismaleimide carbon fiber composites (BMI-CFs), 199
- Bismaleimides (BMIs), 193
- Bisphenol E cyanate ester (BECy), 193
- Blow molding, 10–11

C

- Capsules, 176–178
- Carbon fiber, 7
- Carbon fiber-reinforced polymer (CFRP), 183
- Carbon nanotubes (CNTs), 175–176
- Cellulose acetate (CA), 116
 - biocompatibility of, 116
 - electrical conductivity of, 116
- Cellulose fiber, 46
- Cellulose nanocrystals (CNCs), 79–80
- Cellulose nanofiber (CNF), 143–144
- Ceramics matrix composites, 266
- Chassis, 11–12
- Chitosan (CTS), 145
 - crystallinity of, 80
 - TGA/DSC curves for, 106*f*
- Chloroform, 248–249
- Citric acid, 145
- Collagen, 76
- Compression molding, 121, 135
- Corona discharge, 8
- Critical length, 62–63
- Cyanate esters, 193
- Cyanoacrylates, 193

D

- Dicyclopentadiene (DCPD), 56–57
- Diels–Alder reaction, 175

E

- Electromagnetic interference (EMI), 160
- Epoxy resin, 192–193
- Extracellular matrix (ECM), 219–220
- Extrusion, 10, 120–121

F

- Ferroelectricity, 161
- Fiber, 119
 - continuous, 119
 - discontinuous, 119
 - hybrid, 119
- Fiber-reinforced composite (FRC), 114
- Fiber-reinforced polymer (FRP), 12, 265
 - composite structure, 266
 - contamination, 272–273
 - damage, 267–271
 - assessment, 268–269
 - dent in sandwich structure, 269–270, 270*f*
 - heat, 271, 272*f*
 - impact on monolithic laminate structure, 269
 - laminates splitting, 270, 271*f*
 - puncture and bolt hole, 270, 271*f*
 - guidelines, 271–272
 - industry specific based repair techniques
 - aerospace industry, 276
 - automotive industry, 276
 - marine industry, 277
 - matrix, 265–266
 - procedure, 272
 - reinforcement, 266
 - repair techniques
 - cosmetic/nonstructural repair, 273, 273*f*
 - patch/plug repair, 273–274, 274*f*
 - resin injection repair method, 273
 - scarf joint repair, 275
 - self-repairing/self-healing composites, 275–276
 - structural mechanical fastened doubler, 274–275
- Filament winding, 122, 122*f*, 136–137, 138*f*
- Filler, 77–78
- Finite element (FE) simulation, 206
- Fourier transform infrared spectroscopy (FTIR), 175, 248–250
 - examination, 254
 - results, 256
- 2,5-furandicarboxylic acid (FDCA), 107

G

- Glass fiber, 7, 167
- Graphene oxide (GO), 163

H

- Halloysite nanotubes (HNTs), 245, 247–248
 - fabrication of, 251–253
 - incorporation of, 260
 - surface differences between neat, 257
- 1,6-hexanediol (HDO), 14–15
- Hydrogel, 74
- Hydroxyapatite (HAp), 81–82

I

- Injection, 194–195
 - manual resin, 196, 196*f*
 - molding, 121
 - under pressure and vacuum, 196–197
 - through-thickness vacuum-assisted, 197–198
- In situ polymerization, 120
- Internal defects, 64
- Ionomeric polymer–metal composites (IPMCs), 161

L

- Large visible impact damages (LVIDs), 185
- LASER technology, treatment by, 9
- Lennard-Jones (LJ) potential, 236–237
- Lignin, 228–229
- Linear density, 52

M

- Marine industry, 277
- Materials selection
 - biocomposites
 - in biomedical sectors, 145–148
 - mechanical properties of, 138–145
 - biomaterials, 132–134
 - poly(3-hydroxybutyrate-co-3-hydroxyvalerate), 134
 - polyhydroxybutyrate, 134
 - polylactic acid, 133
 - poly-L-lactide, 133–134
 - thermoplastic starch, 132
- processing techniques, 135–138
 - compression molding, 135
 - filament winding, 136–137, 138*f*
 - injection molding, 136, 137*f*
 - pultrusion process, 137–138, 138*f*
 - resin transfer molding, 135
 - thermoforming, 135

- vacuum-assisted resin transfer molding, 135–136, 136*f*
- ranking method, 131–132
 - AHP method, 131
 - TOPSIS method, 131–132
 - VIKOR method, 132
- screening method, 131
- Meaning of materials (MoM), 130
- Melt compounding (MC), 248
- Metal matrix composites (MMCs), 265–266
- Milling process, 80
- Morphed graphene, 80–81
- Morphology, 250
- Multicriteria decision-making (MCDM), 130
- Multifunctionalized graphene oxide (mfGO), 178–179
- Multiwalled carbon nanotubes (MWCNT), 145
- Murray's law, 177

N

- Nanodiamond, 78–79
 - biocompatibility of, 79
 - production, 79
 - surface chemistry of, 78–79
- Nanofiller, 109
- Natural fibers, 117
 - characteristics, 118*t*
 - characterization of, 50–53
 - chemical composition and mechanical properties of, 218*t*
 - classification of, 214*f*
 - pseudo-stem banana fibers, 47–48
 - sisal fibers, 48
 - surface treatment of, 48–50
 - types of, 117*f*
- Natural fiber structural insulated panel (NSIPs), 138–139
- Nondestructive evaluation (NDE), 158
- Nondestructive inspection (NDI), 158
- Nondestructive testing (NDT), 158, 184

P

- Petrochemical thermoplastic elastomer (PTPE), 91*f*
- PHBV. *See* Poly(3-hydroxybutyrate-co-3-hydroxyvalerate) (PHBV)
- Piezoelectricity, 176

- PLA. *See* Polylactic acid (PLA)
- Plasma functionalization, 8–9, 8*f*
- Plastic, 246
- PMMA. *See* Polymethylmethacrylate (PMMA)
- Poly(3-hydroxyburate) (PHB), 114–115, 134
- biodegradation of, 115
 - characteristics of, 114
 - homopolymer of, 115
- Poly(3-hydroxybutyrate-*co*-3-hydroxyvalerate) (PHBV), 113–115, 132, 134, 222
- Poly(acryloyl-6-aminocaproic acid) (PAACA), 163
- Poly(l-lactic acid) (PLA), 106–107
- Poly(*N*-isopropyl acrylamide), 178–179
- Poly(*N*-vinylpyrrolidone), 176
- Poly(*N,N*-dimethyl acrylamide), 178–179
- Poly(phenylene ether) (PPE), 164
- Poly(vinylidene fluoride) (PVDF), 161, 176
- Poly(L-lactic acid) (PLLA), 115–116, 232–233
- Polyacrolactone (PCL), 14–15
- Polyacrylonitrile (PAN), 7
- Polyamide (PA), 5, 106–107
- Polyaniline, 161
- Polybutylene succinate (PBS), 27
- Polybutylene terephthalate, 6
- Polycaprolactone (PCL), 27
- Polycarbonate (PC), 6, 164
- Polyesteramide (PPKO), 14–15
- Polyester resin, 194
- Poly-ether-ether-ketone (PEEK), 13, 40–41
- Polyethylene (PE), 5, 40–41, 106–107
- Polyethylene terephthalate (PET), 6
- Polyglycolic acid (PGA), 27
- Polyhydroxyalkanoate (PHA), 27–28
- Polyhydroxyalkonate (PHA), 113–114
- Polyhydroxybutyrate (PHB), 132, 134
- Polyimides, 193
- Polylactic acid (PLA), 17, 27, 115, 132–133, 222, 245–247
- fabrication of, 251–253
 - glucose, 223
 - glycerol, 223
 - life cycle of bioplastic, 247*f*
 - mechanical recycling of, 223–225
 - sorbitol, 223
 - synthesis of, 223*f*
 - thermally recycled, 223
- Poly-L-lactic acid (PLLA), 132–134
- Polymer matrix composites (PMCs), 265
- Polymethylmethacrylate (PMMA), 6, 106–107, 136
- Polyoxymethylene, 6
- Polyoxymethylene urea (PMU), 168
- Polyphenylsulfide (PPS), 20
- Polypropylene (PP), 4, 40–41
- Polypyrrole (PPy), 161, 178–179
- Polystyrene, 5
- Polythiophene, 161
- Polyurethane (PUR), 4–5, 56–57
- Polyvinyl alcohol (PVA), 40–41
- Polyvinyl chloride (PVC), 4–5
- PP. *See* Polypropylene (PP)
- Pultrusion, 121, 122*f*
- method, 55
 - process, 137–138, 138*f*
- ## R
- Radiographic testing, 189
- Rapid prototyping, 105–106
- Reaction injection molding (RIM), 55–57, 57*f*
- Recyclability, 220–225
- Recycled cellulose fibers (RCFs), 222
- Recycled newspaper cellulose fibers (RNCFs), 222
- Reinforcement, 6–7
- aramid fiber, 6
 - basalt fiber, 7
 - carbon fiber, 7
 - glass fiber, 7
 - modification, 8–10
 - chemical methods, 9–10
 - physical methods, 8–9
- Resin transfer molding (RTM), 55–56, 56*f*, 122, 135

S

Scanning electron microscopy (SEM), 49–50, 174

Selective laser sintering, 106–107

Self-healing materials, 34, 173–174, 226–229

 - autonomic, 175–178
 - extrinsic healing materials, 176–178

Self-healing materials (*Continued*)
 intrinsic healing materials, 175–176
 characterization of, 174–175
 classification of, 35*f*
 concept, 159
 conventional repairing process
 bonded composite repair, 157
 “in situ curing” of resin, 158
 nondestructive methods, 158–159
 welding/fusion bonding, 157–158
 extrinsic self-healing, 156, 166–168
 glass fibers, 167
 hollow glass tubes, 167
 microcapsules, 168
 three-dimensional microvascular
 networks, 167–168
 intrinsic self-healing, 156, 163–166
 chemical interaction, 164–165
 physical interaction, 163–164
 on supramolecular interactions,
 165–166
 nonautonomic, 178–179
 polymer composites
 with electrically conductive properties,
 160
 electromagnetic, 160
 electromechanical, 161
 magnetic, 161–162
 thermally conductive, 162–163
 Self-healing polymers (SHPs), 227
 Sheet molding compound (SMC), 121
 Shielding usefulness (SE), 160
 Simulated body fluid (SBF), 82
Sisal (*Agave sisalana*), 48
 Sodium hydroxide (NaOH), 49–50
 Solution casting (SC), 245, 248–249
 Statistical Package for Social Scientists
 (SPSS), 46–47
 Structural insulated panels (SIPs), 138–139
 Styrene-(ethylene-butene)-styrene (SEBS),
 141–142
 Supramolecular polymers, 175
 Surface grafting, 9
 Surface modification
 enzyme, 9
 of synthetic fibers by aqueous solutions, 10
 Surface wettability (contact angle), 250, 254
 of films, 257–258

Sustainable biocomposite development
 alginate acid, 248
 biomaterials for plastic films, 246–247
 halloysite nanotubes, 247–248
 materials
 contact angle test, 254
 fabrication of polylactic acid neat film
 sample, 251
 Fourier transform infrared
 spectroscopy, 250
 FTIR examination, 254
 mechanical test, 249
 melt compounding, 248
 microscope examination, 254
 microtensile test, 249
 morphological test, 250
 preparation of, 250
 processing of polylactic acid-based
 films, 249
 solution casting, 248–249
 surface wettability, 250
 transparency test, 254–255
 plastic, 246
 Synthetic polymer, 76–77

T

Tapered double-cantilever beam (TDCB), 163
 Technique of Order Preference Similarity to
 the Ideal Solution (TOPSIS),
 131–132
 Tension–shear chain models (TSCMs), 237
 Terephthalic acid (TPA), 107
 Thermal interface materials (TIMs), 162
 Thermoforming, 11, 121, 135
 Thermography, 189–191
 Thermoplastic elastomers (TPE), 107
 Thermoplastic starch (TPS), 43, 116
 3D bioprinting, 33
 regenerative medicine, 33*f*
 tissue engineering, 33*f*
 3D printing, 105–106
 Time–temperature–moisture superposition
 principle (TTMSP), 234–235
 Transmission electron microscopy, 175
 Transparency of films, 258–259, 259*f*
 Transparency test, 254–256
 Tris(hydroxymethyl) aminomethane
 (TRIS), 16

U

- Ultrasonic testing, 189
- Uncondensed lignin (uLGN),
234–235
- Urea-formaldehyde (UF), 176

V

- Vacuum-assisted resin injection device
(VARID), 201–203, 203*f*
- Vacuum-assisted resin transfer molding
(VARTM), 135–136, 136*f*

Vapor deposition technique, 9

Vascular networks, 177–178

Vinyl ester resin, 194

Viscosity, 44

Visual inspection, 188–189

Vlsekriterijska Optimizacija I
Komoromisno Resenje (VIKOR),
131–132

W

Welding/fusion bonding, 157–158